


BIMA 2.0 3PH., DOUBLE, QPAR51

BIMA 2.0, 3~ spot, DOUBLE, QPAR51, 2 x 10 W, white

The BIMA 2.0 3~ Spot is a ceiling track system luminaire with two spotlights, each equipped with a QPAR51 socket and a power rating of 10 watts per spotlight. The housing is made of aluminium and plastic, ensuring a robust and functional design. With dimensions of 12.7 cm width, 8.2 cm length, and 8.1 cm height, the luminaire is compactly designed. It is intended for indoor use and features an IP20 protection rating as well as an impact resistance of IK class 02. Installation is carried out on a ceiling track system, allowing for flexible orientation of the light source.



Recommended light bulbs

1005079	LED lightbulb QPAR51, GU10, 3000 K, white
1012469	LED PAR16 Smart, GU10, Tunable White, Zigbee

Item no.	1011766
Socket	GU10
Number of sockets	2
Tilt range	90°
Horizontal rotation range	350°
IP Code	IP20
Impact resistance class	IK02
Assembly	Track
Assembly details	Ceiling,
Primary nominal voltage	220-240V ~ 50/60Hz
Safety class	II
Wattage	10 W
Minimum ambient temperature	-20°C
Maximum ambient temperature	40°C
Color	white
Length	8.2 cm
Width	12.7 cm
Height	8.1 cm
Net weight	0.3 kg
Gross weight	0.38 kg
BIG WHITE Page	563

Accessories

1011749	ENOLA 2.0/BIMA 2.0 M, Decorative ring, Ø 54 mm, black
1011750	ENOLA 2.0/BIMA 2.0 M, decorative ring, Ø 54 mm, white
1011751	ENOLA 2.0/BIMA 2.0 M, decorative ring, Ø 54 mm, gold
1011752	ENOLA 2.0/BIMA 2.0 M, decorative ring, Ø 54 mm, copper