


MEDO® HYVE 40 | CL, PHASE

MEDO® HYVE 40, CL, PHASE, Ceiling Surface-Mounted Luminaire, 3000/4000 K, 16 W, 80°, white

The MEDO® HYVE 40 is a ceiling surface-mounted luminaire designed for indoor use. It features PHASE-cut dimming and provides a light output of 16 watts with a colour temperature of 3000 or 4000 Kelvin and a beam angle of 80 degrees. The housing is made of aluminium and steel, with the luminaire having a diameter of 38 centimetres and a height of 6 centimetres. The IP20 protection rating allows for use in dry, dust-protected environments. The MEDO® HYVE 40 is designed for applications requiring reliable and dimmable lighting.



Item no.	1011850
Lamps included	No
IP Code	IP20
Assembly	Surface
Assembly details	Ceiling,
Dimmable	true
Dimming technology	trailing edge
Number of through-wires	40
Primary nominal voltage	220-240V ~ 50/60Hz
Secondary power / voltage	400 mA
Safety class	I
Wattage	16 W
Maximum ambient temperature	45°C
Number of luminaires at LS B16A	56.0
Number of luminaires at LS C16A	118.0
Level of inrush current	5 A
Duration of inrush current	300 µs
Beam angle	80°
Color	white
CRI	90
UGR ≤	16
LXXBXX data	L80B10
Service life	60 000 h
Risk Group	1
Height	6 cm
Diameter	38 cm
Net weight	2.8 kg
Gross weight	3.9 kg
BIG WHITE Page	202

Accessories

1011779	MEDO 2 SUSPENSION KIT, 1.5 m Pendant Length, Central, black
1011780	MEDO 2 SUSPENSION KIT, 1.5 m Pendant Length, Central, white
1011781	MEDO 2 SUSPENSION KIT, 5 m Pendant Length, Central, black
1011782	MEDO 2 SUSPENSION KIT, 5 m Pendant Length, Central, white
1011783	MEDO 2 SUSPENSION KIT, 3 m Pendant Length, Parallel, black
1011784	MEDO 2 SUSPENSION KIT, 3 m Pendant Length, Parallel, white