


MEDO® HYVE 40 | CL, DALI

MEDO® HYVE 40, CL, DALI, Ceiling Surface-Mounted Luminaire, 3000/4000 K, 17 W, 80°, white

The MEDO® HYVE 40 is a surface-mounted ceiling luminaire designed for indoor use. It offers a luminous flux of 2100 lumens with a choice of colour temperatures at 3000 or 4000 Kelvin and a beam angle of 80 degrees. The luminaire is equipped with DALI 2 and touch dimming functions, allowing for flexible light control. The housing is made of aluminium and steel, with a diameter of 38 centimetres and a height of 6 centimetres. The IP20 protection rating classifies the luminaire as suitable for dust-protected indoor areas without direct water protection. The MEDO® HYVE 40 is designed for professional applications requiring efficient and dimmable ceiling lighting.



Item no.	1011852
IP Code	IP20
Assembly	Surface
Assembly details	Ceiling,
Dimmable	true
Dimming technology	DALI 2Touch
Number of through-wires	40
Primary nominal voltage	200-240V ~ 0/50/60Hz
Secondary power / voltage	400 mA
Safety class	I
Wattage	17 W
Maximum ambient temperature	45°C
Number of luminaires at LS B16A	37.0
Number of luminaires at LS C16A	62.0
Level of inrush current	1.476 A
Duration of inrush current	234 µs
Beam angle	80°
Color	white
CRI	90
UGR ≤	16
LXXBXX data	L80B10
Service life	60 000 h
Risk Group	1
Height	6 cm
Diameter	38 cm
Net weight	2.8 kg
Gross weight	3.9 kg
BIG WHITE Page	202

Accessories

1011779	MEDO 2 SUSPENSION KIT, 1.5 m Pendant Length, Central, black
1011780	MEDO 2 SUSPENSION KIT, 1.5 m Pendant Length, Central, white
1011781	MEDO 2 SUSPENSION KIT, 5 m Pendant Length, Central, black
1011782	MEDO 2 SUSPENSION KIT, 5 m Pendant Length, Central, white
1011783	MEDO 2 SUSPENSION KIT, 3 m Pendant Length, Parallel, black
1011784	MEDO 2 SUSPENSION KIT, 3 m Pendant Length, Parallel, white