


MEDO® HYVE 60 | CL, PHASE

MEDO® HYVE 60, CL, PHASE, Ceiling Surface-Mounted Luminaire, 3000/4000 K, 35 W, 80°, black

The surface-mounted ceiling light HYVE 60 from the MEDO® product line is designed for indoor use. It offers a luminous flux of 4800 lumens and a declared service life of 60,000 hours. The housing is made of aluminium and steel, with the luminaire having a diameter of 58.5 cm and a height of 6 cm. Dimming is carried out via trailing edge phase control. The luminaire has a protection rating of IP20, making it suitable for protected indoor areas.



Item no.	1011855
IP Code	IP20
Assembly	Surface
Assembly details	Ceiling,
Dimmable	true
Dimming technology	trailing edge
Number of through-wires	30
Primary nominal voltage	220-240V ~ 50/60Hz
Secondary power / voltage	900 mA
Safety class	I
Wattage	35 W
Maximum ambient temperature	45°C
Number of luminaires at LS B16A	72.0
Number of luminaires at LS C16A	72.0
Level of inrush current	5 A
Duration of inrush current	100 µs
Beam angle	80°
Color	black
CRI	90
UGR ≤	13
LXXBXX data	L80B10
Service life	60 000 h
Risk Group	1
Height	6 cm
Diameter	58.5 cm
Net weight	6.7 kg
Gross weight	8.1 kg
BIG WHITE Page	202

Accessories

1011779	MEDO 2 SUSPENSION KIT, 1.5 m Pendant Length, Central, black
1011780	MEDO 2 SUSPENSION KIT, 1.5 m Pendant Length, Central, white
1011781	MEDO 2 SUSPENSION KIT, 5 m Pendant Length, Central, black
1011782	MEDO 2 SUSPENSION KIT, 5 m Pendant Length, Central, white
1011783	MEDO 2 SUSPENSION KIT, 3 m Pendant Length, Parallel, black
1011784	MEDO 2 SUSPENSION KIT, 3 m Pendant Length, Parallel, white