


MEDO® HYVE 60 | CL, DALI

MEDO® HYVE 60, CL, DALI, Ceiling Surface-Mounted Luminaire, 3000/4000 K, 33 W, 80°, black

The MEDO® HYVE 60 is a surface-mounted ceiling luminaire suitable for indoor use, for example in offices or public buildings. It offers a luminous flux of 4800 lumens with a colour temperature of 3000 or 4000 Kelvin and a beam angle of 80 degrees. The luminaire is equipped with DALI-2 and touch dimming functions, allowing flexible light control. The housing is made of aluminium and steel, with a diameter of 58.5 cm and a height of 6 cm. Its IP20 protection rating permits use in protected indoor areas. The combination of robust materials and modern control technology makes the MEDO® HYVE 60 a functional solution for a wide range of lighting requirements.



Item no.	1011857
IP Code	IP20
Assembly	Surface
Assembly details	Ceiling,
Dimmable	true
Dimming technology	DALI 2Touch
Number of through-wires	30
Primary nominal voltage	200-240V ~ 0/50/60Hz
Secondary power / voltage	900 mA
Safety class	I
Wattage	33 W
Maximum ambient temperature	45°C
Number of luminaires at LS B16A	37.0
Number of luminaires at LS C16A	61.0
Level of inrush current	1.594 A
Duration of inrush current	220 µs
Beam angle	80°
Color	black
CRI	90
UGR ≤	13
LXXBXX data	L80B10
Service life	60 000 h
Risk Group	1
Height	6 cm
Diameter	58.5 cm
Net weight	6.7 kg
Gross weight	8.1 kg
BIG WHITE Page	203

Accessories

1011779	MEDO 2 SUSPENSION KIT, 1.5 m Pendant Length, Central, black
1011780	MEDO 2 SUSPENSION KIT, 1.5 m Pendant Length, Central, white
1011781	MEDO 2 SUSPENSION KIT, 5 m Pendant Length, Central, black
1011782	MEDO 2 SUSPENSION KIT, 5 m Pendant Length, Central, white
1011783	MEDO 2 SUSPENSION KIT, 3 m Pendant Length, Parallel, black
1011784	MEDO 2 SUSPENSION KIT, 3 m Pendant Length, Parallel, white