


MEDO® HYVE 80 | CL, PHASE

MEDO® HYVE 80, CL, PHASE, surface-mounted ceiling luminaire, 3000/4000 K, 70 W, 80°, black

The MEDO® HYVE 80 is a surface-mounted ceiling luminaire designed for indoor use. It delivers a luminous flux of 9700 lumens with a colour temperature of 3000 or 4000 Kelvin and a beam angle of 80 degrees. The luminaire features PHASE-cut dimming and is housed in an aluminium and steel casing. With a diameter of 77 cm and a height of 6 cm, it is compactly designed. The IP20 protection rating provides protection against contact and solid foreign objects. The MEDO® HYVE 80 is particularly suitable for applications requiring powerful, dimmable ceiling lighting.



Item no.	1011859
IP Code	IP20
Assembly	Surface
Assembly details	Ceiling,
Dimmable	true
Dimming technology	trailing edge
Number of through-wires	15
Primary nominal voltage	220-240V ~ 50/60Hz
Secondary power / voltage	1800 mA
Safety class	I
Wattage	70 W
Maximum ambient temperature	45°C
Number of luminaires at LS B16A	72.0
Number of luminaires at LS C16A	72.0
Level of inrush current	5 A
Duration of inrush current	100 µs
Beam angle	80°
Color	black
CRI	90
UGR ≤	13
LXXBXX data	L80B10
Service life	60 000 h
Risk Group	1
Height	6 cm
Diameter	77 cm
Net weight	10.3 kg
Gross weight	13 kg
BIG WHITE Page	203

Accessories

1011779	MEDO 2 SUSPENSION KIT, 1.5 m Pendant Length, Central, black
1011780	MEDO 2 SUSPENSION KIT, 1.5 m Pendant Length, Central, white
1011781	MEDO 2 SUSPENSION KIT, 5 m Pendant Length, Central, black
1011782	MEDO 2 SUSPENSION KIT, 5 m Pendant Length, Central, white
1011783	MEDO 2 SUSPENSION KIT, 3 m Pendant Length, Parallel, black
1011784	MEDO 2 SUSPENSION KIT, 3 m Pendant Length, Parallel, white