


MEDO® HYVE 80 | CL, DALI

MEDO® HYVE 80, CL, DALI, surface-mounted ceiling luminaire, 3000/4000 K, 67 W, 80°, white

The MEDO® HYVE 80 is a surface-mounted ceiling luminaire designed for indoor use. It offers a power output of 67 watts and features DALI 2 and touch dimming, allowing for flexible light control. The luminaire produces a light colour of 3000 or 4000 Kelvin with a beam angle of 80 degrees and a luminous flux of 9700 lumens. The housing is made of aluminium and steel, measures 6 centimetres in height, and has a diameter of 77 centimetres. The IP20 rating makes it suitable for dust-protected indoor areas without exposure to moisture. With a lifespan of 60,000 hours, it is designed for long-lasting operation.



Item no.	1011860
IP Code	IP20
Assembly	Surface
Assembly details	Ceiling,
Dimmable	true
Dimming technology	DALI 2Touch
Number of through-wires	15
Primary nominal voltage	200-240V ~ 0/50/60Hz
Secondary power / voltage	1800 mA
Safety class	I
Wattage	67 W
Maximum ambient temperature	45°C
Number of luminaires at LS B16A	36.0
Number of luminaires at LS C16A	36.0
Level of inrush current	9.1 A
Duration of inrush current	174 µs
Beam angle	80°
Color	white
CRI	90
UGR ≤	13
LXXBXX data	L80B10
Service life	60 000 h
Risk Group	1
Height	6 cm
Diameter	77 cm
Net weight	10.3 kg
Gross weight	13 kg
BIG WHITE Page	203

Accessories

1011779	MEDO 2 SUSPENSION KIT, 1.5 m Pendant Length, Central, black
1011780	MEDO 2 SUSPENSION KIT, 1.5 m Pendant Length, Central, white
1011781	MEDO 2 SUSPENSION KIT, 5 m Pendant Length, Central, black
1011782	MEDO 2 SUSPENSION KIT, 5 m Pendant Length, Central, white
1011783	MEDO 2 SUSPENSION KIT, 3 m Pendant Length, Parallel, black
1011784	MEDO 2 SUSPENSION KIT, 3 m Pendant Length, Parallel, white