


MEDO® HYVE 80 | CL, DALI

MEDO® HYVE 80, CL, DALI, Ceiling Surface-Mounted Luminaire, 3000/4000 K, 67 W,

The MEDO® HYVE 80 is a surface-mounted ceiling luminaire designed for indoor use. It delivers a luminous flux of 9,700 lumens with a colour temperature of 3,000 or 4,000 Kelvin and a beam angle of 80°. The luminaire features DALI-2 dimming and touch control, allowing for flexible light adjustment. The housing is made of aluminium and steel, with a diameter of 77 cm and a height of 6 cm. With an IP20 rating, it is suitable for protected indoor areas. The MEDO® HYVE 80 is aimed at specialist retailers, planners, and installers seeking a powerful and dimmable ceiling luminaire for versatile applications.



Item no.	1011861
IP Code	IP20
Assembly	Surface
Assembly details	Ceiling,
Dimmable	true
Dimming technology	DALI 2Touch
Number of through-wires	15
Primary nominal voltage	200-240V ~ 0/50/60Hz
Secondary power / voltage	1800 mA
Safety class	I
Wattage	67 W
Maximum ambient temperature	45°C
Number of luminaires at LS B16A	36.0
Number of luminaires at LS C16A	36.0
Level of inrush current	9.1 A
Duration of inrush current	174 µs
Beam angle	80°
Color	black
CRI	90
UGR ≤	13
LXXBXX data	L80B10
Service life	60 000 h
Risk Group	1
Height	6 cm
Diameter	77 cm
Net weight	10.3 kg
Gross weight	13 kg
BIG WHITE Page	203

Accessories

1011779	MEDO 2 SUSPENSION KIT, 1.5 m Pendant Length, Central, black
1011780	MEDO 2 SUSPENSION KIT, 1.5 m Pendant Length, Central, white
1011781	MEDO 2 SUSPENSION KIT, 5 m Pendant Length, Central, black
1011782	MEDO 2 SUSPENSION KIT, 5 m Pendant Length, Central, white
1011783	MEDO 2 SUSPENSION KIT, 3 m Pendant Length, Parallel, black
1011784	MEDO 2 SUSPENSION KIT, 3 m Pendant Length, Parallel, white