


LINIUS 120 | PD, PHASE, CANOPY

LINIUS 120, PD, PHASE, CEILING ROSE, pendant luminaire, 2700 K, 34 W, 90°, brass-coloured

The pendant light LINIUS 120 is suitable for indoor use, for example in offices or living areas. It features a light colour of 2700 K and a power consumption of 34 watts with a beam angle of 90°. The luminaire is equipped with phase-cut dimming, allowing for stepless brightness adjustment. The housing is made of aluminium and steel, and the canopy is rectangular in shape. The luminaire measures 121 cm in length, 7.9 cm in height, and 0.76 cm in width, with a suspension length of 200 cm. It has an IP20 protection rating and an impact resistance class of IK02. The declared service life is 50,000 hours.



Item no.	1011935
IP Code	IP20
Impact resistance class	IK02
Assembly	Surface
Assembly details	Ceiling suspended,
Dimmable	true
Dimming technology	trailing edge
Number of through-wires	64
Primary nominal voltage	220-240V ~ 0/50/60Hz
Secondary power / voltage	900
Safety class	I
Wattage	34 W
Minimum ambient temperature	0°C
Maximum ambient temperature	45°C
Number of luminaires at LS B16A	64.0
Number of luminaires at LS C16A	128.0
Level of inrush current	15 A
Duration of inrush current	10 µs
Beam angle	90°
Color	brass
CRI	90
LXXBXX data	L80B20
Service life	50 000 h
Risk Group	0
Length	121 cm
Width	0.8 cm
Height	7.9 cm
Pendant length	200.0000 cm
Net weight	2.65 kg