


LINIUS 120 | PD, PHASE, CANOPY

LINIUS 120, PD, PHASE, CEILING ROSE, pendant luminaire, 3000 K, 34 W, 90°, brass-coloured

The pendant light LINIUS 120 is designed for indoor use and is particularly suitable for illuminating living and working areas. It features a luminous flux of 3100 lumens with a colour temperature of 3000 K and a beam angle of 90°, ensuring uniform and glare-free lighting. The luminaire is equipped with PHASE-cut dimming, allowing flexible light control. The housing is made of aluminium and steel, with a rectangular canopy. The dimensions are 121 cm in length, 0.76 cm in width, and 7.9 cm in height, with a suspension length of 200 cm. The protection rating is IP20, and the impact resistance corresponds to IK02. The luminaire offers a declared service life of 50,000 hours.



Item no.	1011937
IP Code	IP20
Impact resistance class	IK02
Assembly	Surface
Assembly details	Ceiling suspended,
Dimmable	true
Dimming technology	trailing edge
Number of through-wires	64
Primary nominal voltage	220-240V ~ 0/50/60Hz
Secondary power / voltage	900
Safety class	I
Wattage	34 W
Minimum ambient temperature	0°C
Maximum ambient temperature	45°C
Number of luminaires at LS B16A	64.0
Number of luminaires at LS C16A	128.0
Level of inrush current	15 A
Duration of inrush current	10 µs
Beam angle	90°
Color	brass
CRI	90
LXXBXX data	L80B20
Service life	50 000 h
Risk Group	0
Length	121 cm
Width	0.8 cm
Height	7.9 cm
Pendant length	200.0000 cm
Net weight	2.65 kg