


LINIUS 120 | PD, PHASE, RECESSED

LINIUS 120, PD, PHASE, RECESSED, pendant luminaire, 2700 K, 34 W, 90°, brass-coloured

The pendant luminaire LINIUS 120 is designed for ceiling installation and is suitable for indoor use. It offers a luminous flux of 3000 lumens with a colour temperature of 2700 K and a beam angle of 90°. Dimming is achieved via trailing edge phase control. The housing is made of aluminium and steel and is finished in a brass colour. The luminaire measures 121 cm in length, 0.76 cm in width, and 7.9 cm in height. The suspension length is 200 cm. With an IP20 protection rating and an impact resistance class of IK02, it is suitable for typical indoor environments. The luminaire is designed for a long service life of 50,000 hours.



Item no.	1011939
IP Code	IP20
Impact resistance class	IK02
Assembly	Recessed
Assembly details	Ceiling,
Dimmable	true
Dimming technology	trailing edge
Number of through-wires	64
Primary nominal voltage	220-240V ~ 0/50/60Hz
Secondary power / voltage	900
Safety class	II
Wattage	34 W
Minimum ambient temperature	0°C
Maximum ambient temperature	45°C
Number of luminaires at LS B16A	64.0
Number of luminaires at LS C16A	128.0
Level of inrush current	15 A
Duration of inrush current	10 µs
Beam angle	90°
Color	brass
CRI	90
LXXBXX data	L80B20
Service life	50 000 h
Risk Group	0
Length	121 cm
Width	0.8 cm
Height	7.9 cm
Pendant length	200.0000 cm
Net weight	2 kg