


LINIUS 120 | PD, PHASE, RECESSED

LINIUS 120, PD, PHASE, RECESSED, pendant luminaire, 3000 K, 34 W, 90°, brass-coloured

Pendant luminaire LINIUS 120 with recessed mounting for ceiling applications, suitable for indoor use. The luminaire has a power consumption of 34 watts and produces a light colour of 3000 Kelvin with a beam angle of 90 degrees, allowing for targeted illumination. The housing is made of aluminium and steel, combined with a rectangular canopy and a round cut-out for ceiling integration. The pendant length is 200 cm, the luminaire measures 121 cm in length, 7.9 cm in height, and 0.76 cm in width. Dimming is performed via phase-cut (Trailing Edge). The protection rating is IP20, and impact resistance is classified as IK02. The declared service life is 50,000 hours.



Item no.	1011941
IP Code	IP20
Impact resistance class	IK02
Assembly	Recessed
Assembly details	Ceiling,
Dimmable	true
Dimming technology	trailing edge
Number of through-wires	64
Primary nominal voltage	220-240V ~ 0/50/60Hz
Secondary power / voltage	900
Safety class	II
Wattage	34 W
Minimum ambient temperature	0°C
Maximum ambient temperature	45°C
Number of luminaires at LS B16A	64.0
Number of luminaires at LS C16A	128.0
Level of inrush current	15 A
Duration of inrush current	10 µs
Beam angle	90°
Color	brass
CRI	90
LXXBXX data	L80B20
Service life	50 000 h
Risk Group	0
Length	121 cm
Width	0.8 cm
Height	7.9 cm
Pendant length	200.0000 cm
Net weight	2 kg