


LINIUS 150 | PD, PHASE, CANOPY

LINIUS 150, PD, PHASE, CEILING ROSE, pendant luminaire, 2700 K, 40 W, 90°, brass-colored

The pendant light LINIUS 150 is suitable for indoor use, for example in residential or commercial spaces. It offers a luminous flux of 3350 lumens with a colour temperature of 2700 K and a beam angle of 90°. The luminaire is equipped with phase-cut dimming, allowing for stepless brightness adjustment. The housing is made of aluminium and steel and is finished in a brass colour. The rectangular ceiling rose ensures stable mounting. With a length of 150 cm, a width of 0.76 cm, and a height of 7.9 cm, the luminaire has a slim design. The pendant length is 200 cm. Protection class IP20 and impact resistance IK02 provide protection against foreign objects and mechanical impacts in indoor environments. The luminaire has a declared service life of 50,000 hours.



Item no.	1011943
IP Code	IP20
Impact resistance class	IK02
Assembly	Surface
Assembly details	Ceiling suspended,
Dimmable	true
Dimming technology	trailing edge
Number of through-wires	64
Primary nominal voltage	220-240V ~ 0/50/60Hz
Secondary power / voltage	1050
Safety class	I
Wattage	40 W
Minimum ambient temperature	0°C
Maximum ambient temperature	45°C
Number of luminaires at LS B16A	6.4e+14
Number of luminaires at LS C16A	128.0
Level of inrush current	15 A
Duration of inrush current	10 µs
Beam angle	90°
Color	brass
CRI	90
LXXBXX data	L80B20
Service life	50 000 h
Risk Group	0
Length	150 cm
Width	0.8 cm
Height	7.9 cm
Pendant length	200.0000 cm
Net weight	2.95 kg