


LINIUS 150 | PD, PHASE, CANOPY

LINIUS 150, PD, PHASE, CEILING ROSE, pendant luminaire, 3000 K, 40 W, 90°, brass-colored

The pendant light LINIUS 150 is designed for indoor use and is particularly suitable for illuminating living and working areas. It provides a luminous flux of 3450 lumens at a colour temperature of 3000 Kelvin and a beam angle of 90 degrees. The luminaire features PHASE-cut dimming, allowing flexible light control. The housing is made of aluminium and steel and comes in a brass finish. With a length of 150 cm and a suspension length of 200 cm, it offers an elegant and functional lighting solution. The rectangular ceiling rose ensures easy installation. The luminaire is rated IP20 for protection and has an impact resistance of IK02. The declared service life is 50,000 hours.



Item no.	1011945
IP Code	IP20
Impact resistance class	IK02
Assembly	Surface
Assembly details	Ceiling suspended,
Dimmable	true
Dimming technology	trailing edge
Number of through-wires	64
Primary nominal voltage	220-240V ~ 0/50/60Hz
Secondary power / voltage	1050
Safety class	I
Wattage	40 W
Minimum ambient temperature	0°C
Maximum ambient temperature	45°C
Number of luminaires at LS B16A	64.0
Number of luminaires at LS C16A	128.0
Level of inrush current	15 A
Duration of inrush current	10 µs
Beam angle	90°
Color	brass
CRI	90
LXXBXX data	L80B20
Service life	50 000 h
Risk Group	0
Length	150 cm
Width	0.8 cm
Height	7.9 cm
Pendant length	200.0000 cm
Net weight	2.95 kg