


# LINIUS 150 | PD, PHASE, RECESSED

**LINIUS 150, PD, PHASE, RECESSED, pendant luminaire, 3000 K, 40 W, 90°, brass-colored**

The LINIUS 150 pendant luminaire is designed for ceiling installation and is suitable for indoor use, for example in offices or retail spaces. It has a power rating of 40 watts and produces a light colour of 3000 Kelvin with a beam angle of 90 degrees, providing uniform and glare-free illumination. The housing is made of aluminium and finished in brass colour. The luminaire features a rectangular canopy shape and a round cut-out. With a length of 150 cm and a suspension length of 200 cm, it is suitable for larger rooms or areas with higher ceilings. Dimming is performed via PHASE-cut (Trailing Edge). Protection class IP20 and impact resistance according to IK02 ensure safe operation in protected indoor areas. The declared service life is 50,000 hours.




| | |
|---|---|
| **Item no.** | 1011949 |
| **IP Code** | IP20 |
| **Impact resistance class** | IK02 |
| **Assembly** | Recessed |
| **Assembly details** | Ceiling, |
| **Dimmable** | true |
| **Dimming technology** | trailing edge |
| **Number of through-wires** | 64 |
| **Primary nominal voltage** | 220-240V ~ 0/50/60Hz |
| **Secondary power / voltage** | 1050 |
| **Safety class** | II |
| **Wattage** | 40 W |
| **Minimum ambient temperature** | 0°C |
| **Maximum ambient temperature** | 45°C |
| **Number of luminaires at LS B16A** | 64.0 |
| **Number of luminaires at LS C16A** | 128.0 |
| **Level of inrush current** | 15 A |
| **Duration of inrush current** | 10 µs |
| **Beam angle** | 90° |
| **Color** | brass |
| **CRI** | 90 |
| **LXXBXX data** | L80B20 |
| **Service life** | 50 000 h |
| **Risk Group** | 0 |
| **Length** | 150 cm |
| **Width** | 0.8 cm |
| **Height** | 7.9 cm |
| **Pendant length** | 200.0000 cm |
| **Net weight** | 2.3 kg |