


LINIUS 120 | PD, DALI, CANOPY

LINIUS 120, PD, DALI, CEILING ROSE, pendant luminaire, 2700 K, 34 W, 90°, brass-coloured

The LINIUS 120 pendant luminaire is designed for indoor use and is particularly suitable for representative lighting tasks. It features a light colour of 2700 K and a luminous flux of 3000 lumens with a power consumption of 34 watts. The luminaire is equipped with a rectangular ceiling rose and allows dimming via the DALI 2 protocol. The housing is made of aluminium and measures 121 cm in length, 7.9 cm in height, and 0.76 cm in width. The pendant length is 200 cm. The light distribution has a beam angle of 90°. The protection rating is IP20, and the impact resistance is classified as IK02. These technical specifications make the luminaire suitable for use in offices, conference rooms, or similar indoor areas where glare-free and dimmable general lighting is required.



Item no.	1011951
Lamps included	No
IP Code	IP20
Impact resistance class	IK02
Assembly	Surface
Assembly details	Ceiling suspended,
Dimmable	true
Dimming technology	DALI 2
Number of through-wires	15
Primary nominal voltage	220-240V ~ 0/50/60Hz
Secondary power / voltage	900
Safety class	I
Wattage	34 W
Minimum ambient temperature	0°C
Maximum ambient temperature	45°C
Number of luminaires at LS B16A	15.0
Number of luminaires at LS C16A	24.0
Level of inrush current	65 A
Duration of inrush current	200 µs
Beam angle	90°
Color	brass
CRI	90
LXXBXX data	L80B20
Service life	50 000 h
Risk Group	0
Length	121 cm
Width	0.8 cm
Height	7.9 cm
Pendant length	200.0000 cm