


LINIUS 120 | PD, DALI, CANOPY

LINIUS 120, PD, DALI, CEILING ROSE, pendant luminaire, 3000 K, 34 W, 90°, brass-coloured

The LINIUS 120 pendant light is designed for indoor use and is particularly suitable for ceiling mounting in residential and work areas. It offers a luminous flux of 3100 lumens with a colour temperature of 3000 K and a beam angle of 90°. The luminaire is equipped with DALI-2 dimming, allowing for flexible light control. The housing is made of aluminium and features a rectangular ceiling rose. Its dimensions are 121 cm in length, 0.76 cm in width, and 7.9 cm in height, with a suspension length of 200 cm. The protection rating is IP20, and the mechanical impact resistance corresponds to IK02. These technical specifications make the LINIUS 120 a functional lighting solution for various indoor requirements.



Item no.	1011953
IP Code	IP20
Impact resistance class	IK02
Assembly	Surface
Assembly details	Ceiling suspended,
Dimmable	true
Dimming technology	DALI 2
Number of through-wires	15
Primary nominal voltage	220-240V ~ 0/50/60Hz
Secondary power / voltage	900
Safety class	I
Wattage	34 W
Minimum ambient temperature	0°C
Maximum ambient temperature	45°C
Number of luminaires at LS B16A	15.0
Number of luminaires at LS C16A	24.0
Level of inrush current	65 A
Duration of inrush current	200 µs
Beam angle	90°
Color	brass
CRI	90
LXXBXX data	L80B20
Service life	50 000 h
Risk Group	0
Length	121 cm
Width	0.8 cm
Height	7.9 cm
Pendant length	200.0000 cm
Net weight	2.65 kg