


LINIUS 150 | PD, DALI, CANOPY

LINIUS 150, PD, DALI, CEILING ROSE, pendant luminaire, 2700 K, 40 W, 90°, brass-coloured

The LINIUS 150 is a pendant luminaire designed for indoor use, for example in offices, reception areas, or conference rooms. It provides a luminous flux of 3350 lumens at a colour temperature of 2700 Kelvin and a beam angle of 90 degrees, ensuring pleasant and even illumination. The luminaire features DALI-2 dimming for flexible light control. The housing is made of aluminium and is equipped with a rectangular ceiling rose. The suspension length is 200 cm, the luminaire measures 150 cm in length, 0.76 cm in width, and 7.9 cm in height. The protection rating is IP20, and the luminaire has an impact resistance of class IK02. The LINIUS 150 is designed for demanding lighting applications and offers a long-lasting lighting solution with a service life of 50,000 hours.



Item no.	1011959
IP Code	IP20
Impact resistance class	IK02
Assembly	Surface
Assembly details	Ceiling suspended,
Dimmable	true
Dimming technology	DALI 2
Number of through-wires	15
Primary nominal voltage	220-240V ~ 0/50/60Hz
Secondary power / voltage	1050
Safety class	I
Wattage	40 W
Minimum ambient temperature	0°C
Maximum ambient temperature	45°C
Number of luminaires at LS B16A	15.0
Number of luminaires at LS C16A	24.0
Level of inrush current	65 A
Duration of inrush current	200 µs
Beam angle	90°
Color	brass
CRI	90
LXXBXX data	L80B20
Service life	50 000 h
Risk Group	0
Length	150 cm
Width	0.8 cm
Height	7.9 cm
Pendant length	200.0000 cm
Net weight	2.95 kg