


LINIUS 150 | PD, DALI, CANOPY

LINIUS 150, PD, DALI, CEILING ROSE, pendant luminaire, 3000 K, 40 W, 90°, brass-coloured

The LINIUS 150 pendant light is designed for indoor use and is particularly suitable for illuminating work and common areas. It offers a luminous flux of 3450 lumens with a colour temperature of 3000 Kelvin and a beam angle of 90 degrees. The luminaire is equipped with DALI 2 dimming, allowing flexible light control. The housing is made of aluminium and features a rectangular ceiling rose. The suspension length is 200 centimetres, with a product length of 150 centimetres and a height of 7.9 centimetres. The luminaire has an IP20 protection rating and an impact resistance of IK class 02. The declared service life is 50,000 hours.



Item no.	1011961
IP Code	IP20
Impact resistance class	IK02
Assembly	Surface
Assembly details	Ceiling suspended,
Dimmable	true
Dimming technology	DALI 2
Number of through-wires	15
Primary nominal voltage	220-240V ~ 0/50/60Hz
Secondary power / voltage	1050
Safety class	I
Wattage	40 W
Minimum ambient temperature	0°C
Maximum ambient temperature	45°C
Number of luminaires at LS B16A	15.0
Number of luminaires at LS C16A	24.0
Level of inrush current	65 A
Duration of inrush current	200 µs
Beam angle	90°
Color	brass
CRI	90
LXXBXX data	L80B20
Service life	50 000 h
Risk Group	0
Length	150 cm
Width	0.8 cm
Height	7.9 cm
Pendant length	200.0000 cm
Net weight	2.95 kg