


LINIUS 150 | PD, DALI RECESSED

LINIUS 150, PD, DALI, RECESSED, pendant luminaire, 2700 K, 40 W, 90°, brass-coloured

The pendant light LINIUS 150 is designed for ceiling installation and is suitable for indoor use. It features a luminous flux of 3350 lumens with a colour temperature of 2700 K and a beam angle of 90°. The luminaire is equipped with a DALI-2 dimming function, allowing flexible light control. The housing is made of aluminium and measures 150 cm in length, 0.76 cm in width, and 7.9 cm in height. The suspension length is 200 cm. With an IP20 rating, the luminaire is suitable for dust-protected indoor areas and has an impact resistance of IK02. The canopy is rectangular, while the cut-out for mounting is round. The declared lifetime of the luminaire is 50,000 hours.



Item no.	1011963
IP Code	IP20
Impact resistance class	IK02
Assembly	Recessed
Assembly details	Ceiling,
Dimmable	true
Dimming technology	DALI 2
Number of through-wires	15
Primary nominal voltage	220-240V ~ 0/50/60Hz
Secondary power / voltage	1050
Safety class	II
Wattage	40 W
Minimum ambient temperature	0°C
Maximum ambient temperature	45°C
Number of luminaires at LS B16A	15.0
Number of luminaires at LS C16A	24.0
Level of inrush current	65 A
Duration of inrush current	200 µs
Beam angle	90°
Color	brass
CRI	90
LXXBXX data	L80B20
Service life	50 000 h
Risk Group	0
Length	150 cm
Width	0.8 cm
Height	7.9 cm
Pendant length	200.0000 cm
Net weight	2.36 kg