


OVANA 44 | PD, LED, PHASE, CCT

OVANA 44, PD, LED, PHASE, CCT, pendant luminaire, 2700/3000/4000 K, 14 W, 115°, black

The OVANA 44 is a pendant luminaire suitable for indoor lighting. It features an adjustable colour temperature of 2700, 3000, and 4000 Kelvin and a luminous flux of 1620 to 1680 lumens with a power consumption of 14 watts. The luminaire has a beam angle of 115° and is compatible with phase-cut and trailing-edge dimming. The housing is made of steel and polycarbonate, and the canopy is ROUND in design. With a diameter of 44 cm, a height of 12 cm, and a suspension length of 200 cm, it is suitable for various ceiling heights. The protection rating is IP20, and the impact resistance corresponds to IK02. The luminaire is designed for use in residential and work areas.



Item no.	1011991
Lamps included	No
Number of different light outlets	1
IP Code	IP20
Impact resistance class	IK02
Assembly	Surface
Assembly details	Ceiling suspended,
Dimmable	true
Dimming technology	Leading edgetrailing edge
Number of through-wires	50
Primary nominal voltage	220-240V ~ 50/60Hz
Secondary power / voltage	350
Safety class	I
Wattage	14 W
Ambient temperature	85
Minimum ambient temperature	-20°C
Maximum ambient temperature	40°C
Number of luminaires at LS B16A	160.0
Number of luminaires at LS C16A	160.0
Level of inrush current	5 A
Duration of inrush current	100 µs
Beam angle	115°
Color	black
CRI	90
UGR ≤	22
LXXBXX data	L80B10
Service life	50 000 h
Risk Group	1
Height	12 cm