


OVANA 44 | PD, LED, PHASE, CCT

OVANA 44, PD, LED, PHASE, CCT, pendant luminaire, 2700/3000/4000 K, 14 W, 115°, white

The OVANA 44 pendant light is designed for indoor use and is particularly suitable for residential and commercial spaces. It features an integrated LED light source with a power consumption of 14 watts and offers a selectable colour temperature of 2700, 3000, or 4000 Kelvin. The beam angle is 115°, ensuring even light distribution. The housing is made of steel and polycarbonate, and the canopy is round in shape. The luminaire has a diameter of 44 cm, a height of 12 cm, and a pendant length of 200 cm. Dimming is compatible with both leading-edge and trailing-edge phase control. The protection rating is IP20, and the impact resistance corresponds to IK02 class. The declared LED lifespan is 50,000 hours.



Item no.	1011992
Number of different light outlets	1
IP Code	IP20
Impact resistance class	IK02
Assembly	Surface
Assembly details	Ceiling suspended,
Dimmable	true
Dimming technology	Leading edgetrailing edge
Number of through-wires	50
Primary nominal voltage	220-240V ~ 50/60Hz
Secondary power / voltage	350
Safety class	I
Wattage	14 W
Ambient temperature	85
Minimum ambient temperature	-20°C
Maximum ambient temperature	40°C
Number of luminaires at LS B16A	160.0
Number of luminaires at LS C16A	160.0
Level of inrush current	5 A
Duration of inrush current	100 µs
Beam angle	115°
Color	white
CRI	90
UGR ≤	22
LXXBXX data	L80B10
Service life	50 000 h
Risk Group	1
Height	12 cm
Diameter	44 cm