


OVANA 30 | CL, LED, PHASE, CCT

OVANA 30, CL, LED, PHASE, CCT, surface-mounted ceiling luminaire, 2700/3000/4000 K, 11 W, 105°, black

The OVANA 30 is a surface-mounted ceiling luminaire suitable for indoor use. It features an LED light source with a power output of 11 watts and offers a variable colour temperature of 2700, 3000, and 4000 Kelvin. The beam angle is 105 degrees, ensuring uniform illumination. The housing is made of steel, combined with a polycarbonate diffuser. The luminaire is designed for PHASE cut-on and cut-off dimming and has an IP20 protection rating. With a diameter of 30 cm and a height of 12 cm, it is compactly designed and suitable for various ceiling installations. The declared LED lifespan is 50,000 hours.



Item no.	1011993
Lamps included	No
Number of different light outlets	1
IP Code	IP20
Assembly	Surface
Assembly details	Ceiling,
Dimmable	true
Dimming technology	Leading edgetrailing edge
Number of through-wires	50
Primary nominal voltage	220-240V ~ 50/60Hz
Secondary power / voltage	250
Safety class	I
Wattage	11 W
Ambient temperature	85
Minimum ambient temperature	-20°C
Maximum ambient temperature	40°C
Number of luminaires at LS B16A	56.0
Number of luminaires at LS C16A	118.0
Level of inrush current	5 A
Duration of inrush current	300 µs
Beam angle	105°
Color	black
CRI	90
UGR ≤	22
LXXBXX data	L80B10
Service life	50 000 h
Risk Group	1
Height	12 cm
Diameter	30 cm