


OVANA 44 | CL, LED, PHASE, CCT

OVANA 44, CL, LED, PHASE, CCT, surface-mounted ceiling luminaire, 2700/3000/4000 K, 14 W, 115°, black

The OVANA 44 is a surface-mounted ceiling luminaire suitable for indoor use. It features an LED light source with a power consumption of 14 watts and offers a variable colour temperature of 2700, 3000, and 4000 Kelvin, allowing flexible adjustment to different lighting atmospheres. The luminaire has a beam angle of 115° and a luminous flux ranging from 1620 to 1680 lumens. The housing is made of steel and polycarbonate, ensuring a robust construction. With a diameter of 44 cm and a height of 12 cm, it is compactly sized. Dimming is achieved via PHASE cut-on and cut-off, enabling easy control of the light level. The protection rating is IP20, providing protection against solid foreign objects larger than 12.5 mm in diameter.



Item no.	1011995
Number of different light outlets	1
IP Code	IP20
Assembly	Surface
Assembly details	Ceiling,
Dimmable	true
Dimming technology	Leading edgetrailing edge
Number of through-wires	50
Primary nominal voltage	220-240V ~ 50/60Hz
Secondary power / voltage	350
Safety class	I
Wattage	14 W
Ambient temperature	85
Minimum ambient temperature	-20°C
Maximum ambient temperature	40°C
Number of luminaires at LS B16A	160.0
Number of luminaires at LS C16A	160.0
Level of inrush current	5 A
Duration of inrush current	100 µs
Beam angle	115°
Color	black
CRI	90
UGR ≤	22
LXXBXX data	L80B10
Service life	50 000 h
Risk Group	1
Height	12 cm
Diameter	44 cm
Net weight	3.71 kg