
OVANA 30 | CL, LED, ZIGBEE, TW

OVANA 30, CL, LED, ZIGBEE, TW, surface-mounted ceiling luminaire, 2200-6500 K, 10 W, 105°, white

The OVANA 30 is a surface-mounted ceiling luminaire designed for indoor use. It features an LED light source with a variable colour temperature ranging from 2200 to 6500 Kelvin and provides a luminous flux of 1120 to 1260 lumens at a power consumption of 10 watts. The luminaire is equipped with dim-to-warm technology and Zigbee wireless control, allowing for flexible light management. The housing is made of steel and polycarbonate, with a beam angle of 105 degrees. With a diameter of 30 centimetres and a height of 12 centimetres, the luminaire has a compact design. The IP20 rating offers protection against solid foreign objects larger than 12.5 mm. The declared LED lifetime is 50,000 hours.



Item no.	1012000
Number of different light outlets	1
IP Code	IP20
Assembly	Surface
Assembly details	Ceiling,
Dimmable	true
Dimming technology	Dim-to-WarmZigbee
Number of through-wires	50
Primary nominal voltage	220-240V ~ 50/60Hz
Secondary power / voltage	250
Safety class	I
Wattage	10 W
Ambient temperature	85
Minimum ambient temperature	-25°C
Maximum ambient temperature	45°C
Number of luminaires at LS B16A	55.0
Number of luminaires at LS C16A	92.0
Level of inrush current	4.32 A
Duration of inrush current	80 µs
Beam angle	105°
Color	white
CRI	90
UGR ≤	22
LXXBXX data	L80B10
Service life	50 000 h
Risk Group	1
Height	12 cm
Diameter	30 cm
Net weight	1.75 kg