


PL-BEAM PRO M | SP, DALI

PL-BEAM PRO M, SP, DALI, wall and ceiling surface-mounted luminaire, 2700 K, 26 W, 64°, anthracite

The LED spotlight PL-BEAM PRO M is designed for wall and ceiling mounting and is suitable for use in demanding indoor and outdoor environments. With a luminous flux of 3200 lumens at 26 watts and a colour temperature of 2700 K, it provides warm white lighting with a beam angle of 64°. The housing is made of aluminium and features a glass cover. The luminaire has a high protection rating of IP66 as well as impact resistance class IK08, making it resistant to dust, jet water, and mechanical impacts. Dimming is carried out via the DALI-2 protocol, allowing for flexible control. With a product height of 19.4 cm and a diameter of 16.2 cm, the luminaire is compactly designed and suitable for a variety of installation situations.



Item no.	1012120
Lamps included	No
IP Code	IP66
Impact resistance class	IK08
Impact resistance	5 Joule
Assembly	Surface
Dimmable	true
Dimming technology	DALI 2
Number of through-wires	30
Primary nominal voltage	220-240V ~ 0/50/60Hz
Secondary power / voltage	700 mA
Safety class	I
Wattage	26 W
Minimum ambient temperature	-20°C
Maximum ambient temperature	50°C
Number of luminaires at LS B16A	37.0
Number of luminaires at LS C16A	62.0
Level of inrush current	24 A
Duration of inrush current	98 µs
Temperature at glass (light emission)	60
Beam angle	64°
Color	anthracite
CRI	80
LXXBXX data	L80B20
Service life	70 000 h
Risk Group	1
Height	19.4 cm
Diameter	16.2 cm
Net weight	1.95 kg

Accessories

1012132	PL-BEAM PRO M, SHADE, anthracite
1012134	PL-BEAM PRO M, HONEYCOMB LOUVRE, black
1012135	PL-BEAM PRO S/M, POLE CLAMP, anthracite
234350	WALL BRACKET, for outdoor spotlights, 80 cm, black