


PL-BEAM PRO M | SP, DALI

PL-BEAM PRO M, SP, DALI, wall and ceiling surface-mounted luminaire, 2200 K, 26 W, 23°, anthracite

The LED spotlight PL-BEAM PRO M is designed for wall and ceiling mounting and is suitable for use in demanding indoor and outdoor areas. With a luminous flux of 3050 lumens and a colour temperature of 2200 K, it produces warm white light with a narrow beam angle of 23°. The housing is made of aluminium and glass, ensuring a robust construction. The luminaire features a DALI 2 dimming function for precise light control. It is protected to IP66 against dust and water ingress and has a high impact resistance of class IK08. The compact dimensions of 16.2 cm diameter and 19.4 cm height allow for flexible installation. The declared service life is 70,000 hours.



Item no.	1012121
Lamps included	No
IP Code	IP66
Impact resistance class	IK08
Impact resistance	5 Joule
Assembly	Surface
Dimmable	true
Dimming technology	DALI 2
Number of through-wires	30
Primary nominal voltage	220-240V ~ 0/50/60Hz
Secondary power / voltage	700 mA
Safety class	I
Wattage	26 W
Minimum ambient temperature	-20°C
Maximum ambient temperature	50°C
Number of luminaires at LS B16A	37.0
Number of luminaires at LS C16A	62.0
Level of inrush current	24 A
Duration of inrush current	98 µs
Temperature at glass (light emission)	60
Beam angle	23°
Color	anthracite
CRI	80
LXXBXX data	L80B20
Service life	70 000 h
Risk Group	1
Height	19.4 cm
Diameter	16.2 cm
Net weight	1.95 kg

Accessories

1012132	PL-BEAM PRO M, SHADE, anthracite
1012134	PL-BEAM PRO M, HONEYCOMB LOUVRE, black
1012135	PL-BEAM PRO S/M, POLE CLAMP, anthracite
234350	WALL BRACKET, for outdoor spotlights, 80 cm, black