





PL-BEAM PRO M | SP, DALI, ASYM

PL-BEAM PRO M, SP, DALI, ASYMMETRIC, wall and ceiling surface-mounted luminaire, 3000 K, 26 W, 25°, anthracite

The LED spotlight PL-BEAM PRO S, SP, DALI, ASYMMETRIC is designed for wall and ceiling mounting and is suitable for indoor and outdoor use with high protection requirements. With a colour temperature of 3000 K and a luminous flux of 3400 lumens, it offers an asymmetric light distribution with a beam angle of 25°. The housing is made of aluminium and glass, ensuring a robust construction. The luminaire is equipped with DALI 2 technology for control and dimming, allowing flexible light management. It features an IP66 protection rating and an impact resistance of IK08, protecting it against dust ingress, powerful water jets, and mechanical impacts. The compact dimensions, with a diameter of 16.2 cm and a height of 19.4 cm, facilitate installation and integration into various applications.



Item no.	1012126
IP Code	IP66
Impact resistance class	IK08
Impact resistance	5 Joule
Assembly	Surface
Dimmable	true
Dimming technology	DALI 2
Number of through-wires	30
Primary nominal voltage	220-240V ~ 0/50/60Hz
Secondary power / voltage	700 mA
Safety class	I
Wattage	26 W
Minimum ambient temperature	-20°C
Maximum ambient temperature	50°C
Number of luminaires at LS B16A	37.0
Number of luminaires at LS C16A	62.0
Level of inrush current	24 A
Duration of inrush current	98 µs
Temperature at glass (light emission)	60
Beam angle	25°
Color	anthracite
CRI	80
LXXBXX data	L80B20
Service life	70 000 h
Risk Group	1
Height	19.4 cm
Diameter	16.2 cm
Net weight	1.95 kg
Gross weight	2.43 kg

Accessories

1012132	PL-BEAM PRO M, SHADE, anthracite
1012134	PL-BEAM PRO M, HONEYCOMB LOUVRE, black
1012135	PL-BEAM PRO S/M, POLE CLAMP, anthracite
234350	WALL BRACKET, for outdoor spotlights, 80 cm, black