




GLENOS® 2.0 | PD, 1.2M, DALI, UGR19

GLENOS® 2.0, PD, 1.2M, DALI, UGR19, Pendant luminaire, Pendant length: 200 cm, 3000 K, 38 W, 80°, white

The GLENOS® 2.0 pendant luminaire is designed for indoor lighting and is particularly suitable for offices, conference rooms, and other work environments. It has a length of 120 cm and a suspension length of 200 cm, allowing flexible integration into room layouts. The luminaire is equipped with an LED light source that delivers a luminous flux of 5950 lumens at a colour temperature of 3000 K. Light distribution is achieved with a beam angle of 80° and a UGR value of 19, ensuring glare-free illumination. The housing is made of aluminium and finished in white. The luminaire features DALI 2 and touch dimming functions, enabling stepless light control. The IP20 protection rating safeguards the luminaire against contact and solid foreign objects.



Item no.	1012154
Number of different light outlets	2
IP Code	IP20
Assembly	Surface
Assembly details	Ceiling suspended,
Dimmable	true
Dimming technology	DALI 2Touch
Number of through-wires	25
Primary nominal voltage	200-240V ~ 0/50/60Hz
Secondary power / voltage	1050 mA
Safety class	I
Wattage	38 W
Maximum ambient temperature	40°C
Number of luminaires at LS B16A	29.0
Number of luminaires at LS C16A	48.0
Level of inrush current	15.88 A
Duration of inrush current	240 µs
Beam angle	80°
Color	white
CRI	80
UGR ≤	19
LXXBXX data	L80B20
Service life	100 000 h
Length	120 cm
Width	4.8 cm
Height	7 cm
Pendant length	200.0000 cm
Net weight	3.8 kg
Gross weight	5.4 kg