


GLENOS® 2.0 | PD, 1.5M, DALI, UGR19

GLENOS® 2.0, PD, 1.5M, DALI, UGR19, Pendant luminaire, Pendant length: 200 cm, 3000 K, 46 W, 80°, black

The GLENOS® 2.0 pendant luminaire is designed for indoor use and is particularly suitable for applications in offices, conference rooms, or representative areas. It features a rectangular shape with a length of 150 cm, a width of 4.8 cm, a height of 7 cm, and a suspension length of 200 cm. The housing is made of aluminium and offers a long service life of up to 100,000 hours. With a luminous flux of 6,700 lumens, the luminaire ensures efficient and uniform illumination. Dimming is controlled via DALI and touch technology, allowing flexible light management. The IP20 protection rating safeguards the luminaire against contact and solid foreign objects, making it suitable for use in protected indoor environments. The luminaire meets the requirements for glare-free lighting with a UGR value of 19.



Item no.	1012159
Number of different light outlets	2
IP Code	IP20
Assembly	Surface
Assembly details	Ceiling suspended,
Dimmable	true
Dimming technology	DALI 2Touch
Number of through-wires	20
Primary nominal voltage	200-240V ~ 0/50/60Hz
Secondary power / voltage	1250 mA
Safety class	I
Wattage	46 W
Maximum ambient temperature	40°C
Number of luminaires at LS B16A	20.0
Number of luminaires at LS C16A	33.0
Level of inrush current	19.5 A
Duration of inrush current	272 µs
Beam angle	80°
Color	black
CRI	80
UGR ≤	19
LXXBXX data	L80B20
Service life	100 000 h
Length	150 cm
Width	4.8 cm
Height	7 cm
Pendant length	200.0000 cm
Net weight	4.3 kg
Gross weight	5.8 kg