


GLENOS® 2.0 | PD, 1.5M, DALI, UGR19

GLENOS® 2.0, PD, 1.5M, DALI, UGR19, Pendant luminaire, Pendant length: 200 cm, 4000 K, 46 W, 80°, white

The GLENOS® 2.0 pendant luminaire is designed for indoor use and is particularly suitable for office and work areas. It has a length of 150 cm and a suspension length of 200 cm, offering flexible installation options. The housing is made of aluminium and is finished in white. The luminaire is equipped with DALI 2 and touch dimming functions, allowing precise light control. With a power consumption of 46 watts, it produces a luminous flux of 7,650 lumens at a colour temperature of 4000 K and a beam angle of 80°. The UGR19 ensures glare-free lighting. The rectangular canopy allows for easy and secure ceiling mounting. The IP20 protection rating is designed for use in dry indoor environments.



Item no.	1012160
Number of different light outlets	2
IP Code	IP20
Assembly	Surface
Assembly details	Ceiling suspended,
Dimmable	true
Dimming technology	DALI 2Touch
Number of through-wires	20
Primary nominal voltage	200-240V ~ 0/50/60Hz
Secondary power / voltage	1250 mA
Safety class	I
Wattage	46 W
Maximum ambient temperature	40°C
Number of luminaires at LS B16A	20.0
Number of luminaires at LS C16A	33.0
Level of inrush current	19.5 A
Duration of inrush current	272 µs
Beam angle	80°
Color	white
CRI	80
UGR ≤	19
LXXBXX data	L80B20
Service life	100 000 h
Length	150 cm
Width	4.8 cm
Height	7 cm
Pendant length	200.0000 cm
Net weight	4.3 kg
Gross weight	5.8 kg