


GLENOS® 2.0 | CL, 1.2M, DALI, UGR22

GLENOS® 2.0, CL, 1.2M, DALI, UGR22, surface-mounted ceiling luminaire, 3000 K, 17 W, black

The surface-mounted ceiling luminaire GLENOS® 2.0 is designed for indoor use and is particularly suitable for office and work areas where glare-free lighting is required. It delivers a luminous flux of 2050 lumens and has a long service life of 100,000 hours. The housing is made of aluminium and measures 120 cm in length, 4.8 cm in width, and 7 cm in height. The luminaire is equipped with DALI and touch dimming functions, allowing flexible light control. With an IP20 rating, it is suitable for dust-protected indoor environments. The luminaire meets the requirements for low glare (UGR22), providing a comfortable and efficient lighting solution for professional applications.



Item no.	1012163
Number of different light outlets	1
IP Code	IP20
Assembly	Surface
Assembly details	Ceiling,
Dimmable	true
Dimming technology	DALI 2Touch
Number of through-wires	25
Primary nominal voltage	200-240V ~ 0/50/60Hz
Secondary power / voltage	450 mA
Safety class	I
Wattage	17 W
Maximum ambient temperature	40°C
Number of luminaires at LS B16A	29.0
Number of luminaires at LS C16A	48.0
Level of inrush current	15.88 A
Duration of inrush current	240 µs
Beam angle	80°
Color	black
CRI	80
UGR ≤	22
LXXBXX data	L80B20
Service life	100 000 h
Length	120 cm
Width	4.8 cm
Height	7 cm
Net weight	3.8 kg
Gross weight	5.2 kg
BIG WHITE Page	167