


# GRIP! S | WL, Ø 3.0CM, ON/OFF SWITCH

**GRIP! S, WL, ON/OFF SWITCH, wall-mounted luminaire, 2700 K, 4.6 W, 29°, white / black**

The GRIP! S surface-mounted wall light is designed for indoor lighting and is particularly suitable for use in living and working areas. It features a colour temperature of 2700 K and a luminous flux of 260 lumens with a power consumption of 4.6 watts. The beam angle is 29°, allowing for targeted light distribution. The housing is made of aluminium and measures 15.5 cm in height, 3 cm in width, and 8.4 cm in depth. The luminaire is equipped with an on/off switch and has an IP20 protection rating as well as IK02 impact resistance. Installation is surface-mounted on the wall.




## Light source

| | |
|---|---|
| 2093820 | A G D |

| | |
|---|---|
| Item no. | 1012178 |
| IP Code | IP20 |
| Impact resistance class | IK02 |
| Impact resistance | 0.2 Joule |
| Assembly | Surface |
| Assembly details | Wall, |
| Primary nominal voltage | 220-240V ~ 50/60Hz |
| Secondary power / voltage | 100 mA |
| Safety class | I |
| Wattage | 5 W |
| Minimum ambient temperature | 0°C |
| Maximum ambient temperature | 35°C |
| Number of luminaires at LS B16A | 224.0 |
| Number of luminaires at LS C16A | 400.0 |
| Level of inrush current | 5 A |
| Duration of inrush current | 100 µs |
| Beam angle | 29° |
| Color | white/black |
| CRI | 90 |
| UGR ≤ | 25 |
| LXXBXX data | L80B10 |
| Service life | 50 000 h |
| Risk Group | 1 |
| Width | 3 cm |
| Height | 15.5 cm |
| Depth | 8.4 |
| Net weight | 0.27 kg |
| Gross weight | 0.38 kg |
| BIG WHITE Page | 328 |

## Accessories

| | |
|---|---|
| **1011829** | GRIP! S, decorative ring, white |
| **1011830** | GRIP! S, decorative ring, black |
| **1011831** | GRIP! S, decorative ring, nickel |
| **1011832** | GRIP! S, decorative ring, gold |
| **1011837** | GRIP! S, HONEYCOMB |