




LIPSY® 2.0 30 | CW, DOME

LIPSY® 2.0 30, CW, DOME, wall and ceiling surface-mounted luminaire, 3000 K / 4000 K, 7.1 W / 11 W, 120°, white / milky

The LIPSY® 2.0 30 is a surface-mounted wall and ceiling luminaire designed for indoor use. It offers a light colour of 3000 K or 4000 K and a light distribution with a beam angle of 120°. The luminaire is available in two power variants of 7.1 W and 11 W, delivering a luminous flux between 900 and 1300 lumens depending on the version. The housing is made of steel, combined with a PMMA cover that distributes the light evenly. With a diameter of 30 cm and a height of 9 cm, the luminaire is compactly designed. It features an IP44 protection rating, providing protection against splashing water, as well as an impact resistance class of IK02. The LIPSY® 2.0 30 is designed for a long service life of up to 50,000 hours.



Item no.	1012182
IP Code	IP44
Impact resistance class	IK02
Impact resistance	0.2 Joule
Assembly	Surface
Assembly details	Ceiling, Wall,
Primary nominal voltage	220-240V ~ 50/60Hz
Secondary power / voltage	160/230mA
Safety class	I
Wattage	7 W
Minimum ambient temperature	-20°C
Maximum ambient temperature	40°C
Number of luminaires at LS B16A	133.0
Number of luminaires at LS C16A	133.0
Level of inrush current	5 A
Duration of inrush current	100 µs
Beam angle	120°
Color	white/milky
CRI	80
UGR ≤	25
LXXBXX data	L80B10
Service life	50 000 h
Risk Group	1
Height	9 cm
Diameter	30 cm
Net weight	0.53 kg
Gross weight	0.95 kg
BIG WHITE Page	390