




LIPSY® 2.0 40 | CW, DOME

LIPSY® 2.0 40, CW, DOME, Wall and Ceiling Surface-Mounted Luminaire, 3000 K / 4000 K, 9 W / 18 W, 120°, white / milky

The LIPSY® 2.0 40 is a surface-mounted wall and ceiling luminaire designed for indoor use. It offers a luminous flux of up to 2350 lumens with a colour temperature of 3000 K or 4000 K and a beam angle of 120°. The housing is made of steel and PMMA, ensuring a robust construction. With a diameter of 40 cm and a height of 12.5 cm, the luminaire is compact in size. The IP44 rating provides protection against splashing water, while the impact resistance corresponds to IK02. The luminaire is available in power ratings of 9 W and 18 W and is suitable for applications requiring uniform and efficient lighting on walls or ceilings.



Item no.	1012186
IP Code	IP44
Impact resistance class	IK02
Impact resistance	0.2 Joule
Assembly	Surface
Assembly details	Ceiling, Wall,
Primary nominal voltage	220-240V ~ 50/60Hz
Secondary power / voltage	75/105/150mA
Safety class	I
Wattage	9 W
Minimum ambient temperature	-20°C
Maximum ambient temperature	40°C
Number of luminaires at LS B16A	133.0
Number of luminaires at LS C16A	133.0
Level of inrush current	5 A
Duration of inrush current	100 µs
Beam angle	120°
Color	white/milky
CRI	80
UGR ≤	22
LXXBXX data	L80B10
Service life	50 000 h
Risk Group	1
Height	12.5 cm
Diameter	40 cm
Net weight	0.81 kg
Gross weight	1.5 kg
BIG WHITE Page	391