
SENSER 2.0 30 | RL, ROUND, PHASE

SENSER 2.0 30, RL, round, PHASE, recessed ceiling luminaire, 3000 K / 4000 K, 25 W, 90°, white

The SENSER 2.0 30 is a round recessed ceiling luminaire designed for indoor use. It offers a selectable colour temperature of 3000 K or 4000 K and a power consumption of 25 watts with a beam angle of 90°. The housing is made of aluminium, while the diffuser is manufactured from polycarbonate. The luminaire has a diameter of 30 cm and a height of 2.4 cm. Dimming is carried out via trailing edge phase cut. The protection rating is IP20, and the luminaire is classified with an impact resistance rating of IK02. The SENSER 2.0 30 is intended for recessed ceiling installation and has a declared lifetime of 50,000 hours.



Item no.	1012204
Lamps included	No
IP Code	IP20
Impact resistance class	IK02
Impact resistance	0.2 Joule
Assembly	Recessed
Assembly details	Ceiling,
Dimmable	true
Dimming technology	trailing edge
Number of through-wires	45
Primary nominal voltage	220-240V ~ 50/60Hz
Secondary power / voltage	500 mA
Safety class	II
Wattage	25 W
Minimum ambient temperature	-20°C
Maximum ambient temperature	40°C
Number of luminaires at LS B16A	100.0
Number of luminaires at LS C16A	100.0
Level of inrush current	5 A
Duration of inrush current	100 µs
Beam angle	90°
Color	white
CRI	90
UGR ≤	22
LXXBXX data	L80B10
Service life	50 000 h
Risk Group	1
Height	2.4 cm
Diameter	30 cm