
SENSER 2.0 24 | RL, ROUND, DALI

SENSER 2.0 24, RL, round, DALI, recessed ceiling luminaire, 3000 K / 4000 K, 18 W, 90°, white

The SENSER 2.0 24 is a ROUND recessed ceiling luminaire designed for indoor installation. It provides a luminous flux of approximately 1800 to 1900 lumens with an energy consumption of 18 watts and is available with a selectable colour temperature of 3000 K or 4000 K. The luminaire features a beam angle of 90 degrees and is equipped with DALI-2 dimming, allowing flexible control of light intensity. The housing is made of aluminium, while the diffuser is made of polycarbonate. With a diameter of 22.5 cm and a height of 2.4 cm, the luminaire has a flat design and is mounted as a ceiling recessed luminaire. The protection rating is IP20, and the luminaire is classified with an impact resistance of IK02. The declared service life is 50,000 hours.



Item no.	1012209
Lamps included	No
IP Code	IP20
Impact resistance class	IK02
Impact resistance	0.2 Joule
Assembly	Recessed
Assembly details	Ceiling,
Dimmable	true
Dimming technology	DALI 2
Number of through-wires	60
Primary nominal voltage	220-240V ~ 50/60Hz
Secondary power / voltage	500 mA
Safety class	II
Wattage	18 W
Minimum ambient temperature	-20°C
Maximum ambient temperature	40°C
Number of luminaires at LS B16A	62.0
Number of luminaires at LS C16A	62.0
Level of inrush current	2.02 A
Duration of inrush current	70 µs
Beam angle	90°
Color	white
CRI	90
UGR ≤	25
LXXBXX data	L80B10
Service life	50 000 h
Risk Group	1
Height	2.4 cm
Diameter	22.5 cm