
SENSER 2.0 24 | RL, SQUARE, DALI

SENSER 2.0 24, RL, square, DALI, recessed ceiling luminaire, 3000 K / 4000 K, 18 W, 90°, white

The SENSER 2.0 24 is a square recessed ceiling luminaire designed for ceiling installation, particularly suitable for indoor use. It delivers a luminous flux of approximately 1900 to 2000 lumens with a colour temperature of 3000 K or 4000 K and a beam angle of 90°. The luminaire features DALI 2 dimming for flexible light control. The housing is made of aluminium combined with a polycarbonate diffuser and measures 22.5 x 22.5 cm with a height of 2.4 cm. It has an IP20 protection rating and an impact resistance class of IK02. With a power consumption of 18 watts, it provides a durable lighting solution with a declared lifetime of 50,000 hours.



Item no.	1012210
Lamps included	No
IP Code	IP20
Impact resistance class	IK02
Impact resistance	0.2 Joule
Assembly	Recessed
Assembly details	Ceiling,
Dimmable	true
Dimming technology	DALI 2
Number of through-wires	60
Primary nominal voltage	220-240V ~ 50/60Hz
Secondary power / voltage	500 mA
Safety class	II
Wattage	18 W
Minimum ambient temperature	-20°C
Maximum ambient temperature	40°C
Number of luminaires at LS B16A	62.0
Number of luminaires at LS C16A	62.0
Level of inrush current	2.02 A
Duration of inrush current	70 µs
Beam angle	90°
Color	white
CRI	90
UGR ≤	22
LXXBXX data	L80B10
Service life	50 000 h
Risk Group	1
Length	22.5 cm
Width	22.5 cm