
SENSER 2.0 12 | CW, ROUND, PHASE

SENSER 2.0 12, CW, round, PHASE, surface-mounted wall and ceiling luminaire, 3000 K / 4000 K, 7.2 W, 90°, white

The SENSER 2.0 12 is a ROUND surface-mounted wall and ceiling luminaire designed for indoor use. It delivers a luminous flux of 550 to 600 lumens with an energy consumption of 7.2 watts and offers a colour temperature of 3000 K or 4000 K with a beam angle of 90°. The housing is made of aluminium, combined with a polycarbonate cover. The luminaire has a diameter of 12 cm and a height of 4 cm. Dimming is carried out via phase-cut (trailing edge). The protection rating is IP20, and the impact resistance is classified as IK02. This luminaire is suitable for applications requiring a compact and functional lighting solution on walls or ceilings.



Item no.	1012213
Lamps included	No
IP Code	IP20
Impact resistance class	IK02
Impact resistance	0.2 Joule
Assembly	Surface
Assembly details	Ceiling,
Dimmable	true
Dimming technology	trailing edge
Number of through-wires	100
Primary nominal voltage	220-240V ~ 50/60Hz
Secondary power / voltage	350 mA
Safety class	I
Wattage	7 W
Minimum ambient temperature	-20°C
Maximum ambient temperature	40°C
Number of luminaires at LS B16A	232.0
Number of luminaires at LS C16A	232.0
Level of inrush current	7.5 A
Duration of inrush current	13 µs
Beam angle	90°
Color	white
CRI	90
LXXBXX data	L80B10
Service life	50 000 h
Risk Group	1
Height	4 cm
Diameter	12 cm
Net weight	0.38 kg