
SENSER 2.0 24 | CW, ROUND, PHASE

SENSER 2.0 24, CW, round, PHASE, surface-mounted wall and ceiling luminaire, 3000 K / 4000 K, 23 W, 90°, white

The SENSER 2.0 24 is a ROUND wall and ceiling surface-mounted luminaire designed for indoor use. It offers a luminous flux of 2250 to 2400 lumens with a power consumption of 23 watts and is available with a light colour of 3000 K or 4000 K and a beam angle of 90°. The luminaire features phase-cut dimming, allowing for easy brightness adjustment. The housing is made of aluminium, complemented by a polycarbonate cover. With a diameter of 22.5 cm and a height of 4 cm, the luminaire is compactly designed. Protection class IP20 and impact resistance IK02 provide basic protection against foreign objects and mechanical influences. This luminaire is suitable for a wide range of indoor applications where reliable and dimmable lighting is required.



Item no.	1012217
Lamps included	No
IP Code	IP20
Impact resistance class	IK02
Impact resistance	0.2 Joule
Assembly	Surface
Assembly details	Ceiling,
Dimmable	true
Dimming technology	trailing edge
Number of through-wires	50
Primary nominal voltage	220-240V ~ 50/60Hz
Secondary power / voltage	700 mA
Safety class	I
Wattage	23 W
Minimum ambient temperature	-20°C
Maximum ambient temperature	40°C
Number of luminaires at LS B16A	100.0
Number of luminaires at LS C16A	100.0
Level of inrush current	5 A
Duration of inrush current	100 µs
Beam angle	90°
Color	white
CRI	90
UGR ≤	25
LXXBXX data	L80B10
Service life	50 000 h
Risk Group	1
Height	4 cm
Diameter	22.5 cm