
SENSER 2.0 30 | CW, SQUARE, PHASE

SENSER 2.0 30, CW, square, PHASE, wall and ceiling surface-mounted luminaire, 3000 K / 4000 K, 28 W, 90°, white

The SENSER 2.0 30 is a square surface-mounted wall and ceiling luminaire designed for indoor use. It features a colour temperature of 3000 K or 4000 K and a luminous output of 28 watts with a beam angle of 90°. The housing is made of aluminium combined with polycarbonate elements and measures 30 x 30 x 4 cm. The luminaire is equipped with phase-cut dimming and offers an IP20 protection rating as well as an impact resistance class of IK02. The durable LED technology ensures a declared service life of 50,000 hours.



Item no.	1012220
Lamps included	No
IP Code	IP20
Impact resistance class	IK02
Impact resistance	0.2 Joule
Assembly	Surface
Assembly details	Ceiling,
Dimmable	true
Dimming technology	trailing edge
Number of through-wires	40
Primary nominal voltage	220-240V ~ 50/60Hz
Secondary power / voltage	700 mA
Safety class	I
Wattage	28 W
Minimum ambient temperature	-20°C
Maximum ambient temperature	40°C
Number of luminaires at LS B16A	100.0
Number of luminaires at LS C16A	100.0
Level of inrush current	5 A
Duration of inrush current	100 µs
Beam angle	90°
Color	white
CRI	90
UGR ≤	22
LXXBXX data	L80B10
Service life	50 000 h
Risk Group	1
Length	30 cm
Width	30 cm