
SENSER 2.0 12 | CW, ROUND, DALI

SENSER 2.0 12, CW, round, DALI, surface-mounted wall and ceiling luminaire, 3000 K / 4000 K, 7 W, 90°, white

The SENSER 2.0 12 is a ROUND surface-mounted wall and ceiling luminaire designed for indoor use. It offers a luminous flux of 550 to 600 lumens at a power consumption of 7 watts and is available with a colour temperature of 3000 K or 4000 K, featuring a beam angle of 90°. The housing is made of aluminium combined with a polycarbonate element and measures 12 cm in diameter with a height of 4 cm. The luminaire is equipped with DALI 2 dimming, allowing flexible light control. It has an IP20 protection rating and an impact resistance classified as IK02, ensuring basic robustness against mechanical influences. The SENSER 2.0 12 is suitable for a wide range of applications in residential and commercial spaces where discreet, functional lighting is required.



Item no.	1012221
Lamps included	No
IP Code	IP20
Impact resistance class	IK02
Impact resistance	0.2 Joule
Assembly	Surface
Assembly details	Ceiling,
Dimmable	true
Dimming technology	DALI 2
Number of through-wires	100
Primary nominal voltage	220-240V ~ 50/60Hz
Secondary power / voltage	350 mA
Safety class	I
Wattage	7 W
Minimum ambient temperature	-20°C
Maximum ambient temperature	40°C
Number of luminaires at LS B16A	96.0
Number of luminaires at LS C16A	112.0
Level of inrush current	316 A
Duration of inrush current	72 µs
Beam angle	90°
Color	white
CRI	90
LXXBXX data	L80B10
Service life	50 000 h
Risk Group	1
Height	4 cm
Diameter	12 cm
Net weight	0.42 kg