
SENSER 2.0 30 | CW, ROUND, DALI

SENSER 2.0 30, CW, round, DALI, wall and ceiling surface-mounted luminaire, 3000 K / 4000 K, 27 W, 90°, white

The SENSER 2.0 30 is a ROUND surface-mounted wall and ceiling luminaire suitable for indoor use. It features a colour temperature of 3000 K or 4000 K and a power consumption of 27 watts with a beam angle of 90°. The housing is made of aluminium, combined with a polycarbonate diffuser. The luminaire has a diameter of 30 centimetres and a height of 4 centimetres. It is equipped with a DALI 2 dimming function, offering flexible control options. The IP20 protection rating and IK02 impact resistance class ensure reliable operation in protected environments. The luminaire is designed for a long service life of up to 50,000 hours.



Item no.	1012227
Lamps included	No
IP Code	IP20
Impact resistance class	IK02
Impact resistance	0.2 Joule
Assembly	Surface
Assembly details	Ceiling,
Dimmable	true
Dimming technology	DALI 2
Number of through-wires	40
Primary nominal voltage	220-240V ~ 50/60Hz
Secondary power / voltage	700 mA
Safety class	I
Wattage	27 W
Minimum ambient temperature	-20°C
Maximum ambient temperature	40°C
Number of luminaires at LS B16A	37.0
Number of luminaires at LS C16A	61.0
Level of inrush current	15.94 A
Duration of inrush current	220 µs
Beam angle	90°
Color	white
CRI	90
UGR ≤	22
LXXBXX data	L80B10
Service life	50 000 h
Risk Group	1
Height	4 cm
Diameter	30 cm