



LEDSTRIP SMD | S

LED STRIP SMD, S, 4000 K, L: 500 cm, 8800 lm

The LED strip is designed for indoor use and is suitable for linear lighting in residential, office, or commercial environments. With a length of 500 cm and a slim profile measuring 0.8 cm in width and 0.12 cm in height, the lighting strip can be mounted flexibly. The light colour is 4000 K, producing a neutral white light, and the luminous flux is 8800 lumens. The housing is made of plastic, and the LED strip has an IP20 protection rating against contact and solid foreign objects. The declared service life is 50,000 hours, allowing for long usage. The LED strip is particularly suitable for applications where uniform, bright illumination is required.

Item no.	1012267
Number of different light outlets	1
IP Code	IP20
Assembly	Surface
Assembly details	Ceiling, Wall,
LED distance	0,63 cm
Safety class	III
Safety class	III
Ambient temperature	65
Minimum ambient temperature	-20°C
Maximum ambient temperature	40°C
Beam angle	120°
CRI	90
Binning	3.0000
LXXBXX data	L80B20
Service life	50 000 h
Risk Group	1
Length	500 cm
Width	0.8 cm
Height	0.1 cm
Net weight	0.07 kg
Gross weight	0.12 kg
BIG WHITE Page	617

Accessories

1012325	LED STRIP QUICK CONNECTOR, clear
1012328	LED STRIP HUB, 2 CONNECTIONS
1012329	LED STRIP HUB, 4 CONNECTIONS
1012305	LED STRIP CONNECTOR SMD, FEED-IN S 8MM, clear
1012310	LED STRIP CONNECTOR SMD, CABLE S 8MM, clear
1012315	LED STRIP CONNECTOR SMD, DIRECT S 8MM, clear
1012320	LED STRIP CONNECTOR SMD, 90° S 8MM, clear