





UNIVERSAL DOWNLIGHT SLIM | RL, PHASE

UNIVERSAL DOWNLIGHT SLIM, RL, PHASE, ceiling recessed luminaire, 2700 K / 3000 K / 4000 K, 6 W, black

The recessed ceiling luminaire is designed for installation in suspended ceilings and is suitable for use in offices, retail spaces, and public buildings. It offers a discreet integration into the room architecture and provides uniform general lighting. The housing is intended for ceiling installation, with the luminaire typically operated using a suitable light source. Details regarding luminous flux, colour temperature, protection rating, or control options are not specified, placing the focus on versatile application and easy installation. The luminaire supports a functional and efficient lighting solution for professional indoor environments.



Item no.	1012624
Lamps included	No
IP Code	IP50/IP65
Impact resistance class	IK08
Impact resistance	5 Joule
Assembly	Recessed
Assembly details	Ceiling,
Dimmable	true
Dimming technology	trailing edge
Number of through-wires	100
Primary nominal voltage	220-240V ~ 50/60Hz
Secondary power / voltage	185 mA
Safety class	II
Wattage	6W
Maximum ambient temperature	40°C
Number of luminaires at LS B16A	30.0
Number of luminaires at LS C16A	50.0
Level of inrush current	3 A
Duration of inrush current	30 µs
Color	black
CRI	90
LXXBXX data	L70B10
Service life	500 000 h
Height	3.1 cm
Diameter	8.6 cm
Net weight	0.18 kg
Gross weight	0.24 kg
Shape of cut-out	round
Installation depth	4 cm