




FRAME CURVE

recessed fitting, LED, 3000K, square, matt white, incl. leaf springs

With our FRAME series we offer you a lighting solution for recessed wall and ceiling installation with minimum space requirements. The LED version is equipped with a durable diode and available in either pure white or warm white light colour. To operate, the FRAME CURVE needs a suitable constant current driver rated at 350mA. The optional accessory includes a connector strip for simplified wiring in addition to the mounting box and flush-mount frame. This luminaire contains built-in LED lamps.



Tekniske data

Item no.	113292
IP klasse	IP20
Montering	Recessed
Monterings detaljer	Wall
Sekundær strøm / spænding	350mA
IP Tæthedsgard	III
Watt	1 W
Lumen	60 lm
Farvetemperatur	3000 Kelvin
Farve	white
CRI	90
LXXBXX-data	L70B50
Bredde	9 cm
Højde	9 cm
Dybde	4 cm
Nettovægt	0.148 kg
Bruttovægt	0.207 kg
Indbygnings længde	8.1 cm
Indbygningsbredde	6.9 cm
Indbygningsdybde	4.5 cm
BIG WHITE side	239

Lyskilde

954799	
--------	---

Tilbehør

111861	CABLE EXTENSION , for items with a 350mA plug, 1 m
112781	MOUNTING BOX , for FRAME BASIC, FLAT FRAME BASIC, FLAT FRAME CURVE and FRAME CURVE
111850	MULTIWAY CONNECTOR , 3 outputs with two bridges, black, max. 350-mA
112780	FLUSH-MOUNTED , FRAME, for FRAME BASIC, FLAT FRAME BASIC, FLAT FRAME CURVE and FRAME CURVE
1007270	LED driver 3W , 350mA including AMP socket