




NEW TRIA 1 SET

recessed fitting, LED, 2700K, round, matt black, 38°, incl. driver, clip springs


The simplicity and effectiveness of the NEW TRIA 1 SET is captivating. It is available in matt black, white, or brushed aluminium, in round or square form as well as single-headed or as multi-lamp. Equipped with a powerful, warm white premium COB LED in a tiltable mount, as well as LED driver included in the scope of supply, the set can be used in any lighting situation. The electrical connection is made directly to the 230V mains supply.



TECHNICAL DATA

Item no.	113870
IP Code	IP 20
Assembly	Recessed
Assembly details	Ceiling
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	350 mA
Safety class	II
Wattage	8 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Level of inrush current	11 A
Duration of inrush current	20 µs
Stroboscopic effect (SVM)	0.02
Lumen	645 lm
Colour temperature	2700 Kelvin
Beam angle	38 °
Color	black
CRI	80
LXXBXX data	L70B50
Service life	40000 h
Height	3.5 cm
Diameter	9.3 cm

Light Source

916320		Net weight	0.225 kg
		Gross weight	0.278 kg
		Shape of cut-out	round
		Installation depth	4 cm
		Installation diameter	7.7 cm