




NEW TRIA 1 SET

recessed fitting, single-headed LED, 2700K, square, white, 38°, 9.1W, incl. driver, clip springs


The simplicity and effectiveness of the innovative NEW TRIA 1 SET is captivating. It is available in matt black, white, or brushed aluminium, in round or square form as well as single-headed or as multi-lamp. Equipped with a powerful, warm white premium COB LED in a tiltable mount, as well as LED driver included in the scope of supply, the set can be used in any lighting situation. The electrical connection is made directly to the 230V mains supply.



TECHNICAL DATA

| | |
|-----------------------------|-------------------|
| Item no. | 113881 |
| IP Code | IP 20 |
| Assembly | Recessed |
| Assembly details | Ceiling |
| Primary nominal voltage | 220-240V ~50/60Hz |
| Secondary power / voltage | 350 mA |
| Safety class | II |
| Wattage | 8 W |
| Minimum ambient temperature | -20 °C |
| Maximum ambient temperature | 40 °C |
| Level of inrush current | 11 A |
| Duration of inrush current | 20 µs |
| Stroboscopic effect (SVM) | 0.02 |
| Lumen | 645 lm |
| Colour temperature | 2700 Kelvin |
| Beam angle | 38 ° |
| Color | white |
| CRI | 80 |
| LXXBXX data | L70B50 |
| Service life | 40000 h |
| Length | 9 cm |
| Width | 9 cm |

Light Source

| | | | |
|--------|---|-----------------------|----------|
| 916320 |  | Height | 3.5 cm |
| | | Net weight | 0.24 kg |
| | | Gross weight | 0.292 kg |
| | | Shape of cut-out | round |
| | | Installation depth | 4 cm |
| | | Installation diameter | 7.7 cm |