




NEW TRIA 1 SET

recessed fitting, LED, 3000K, round, white, 30°, 29W
incl. driver, clip springs

The simplicity and effectiveness of the NEW TRIA 1 SET is captivating. It is available in black, white, or brushed aluminium, in round or square form as well as single-headed or as multi-lamp. Equipped with a powerful, warm white premium COB LED in a tiltable mount, as well as LED driver included in the scope of supply, the set can be used in any lighting situation. The electrical connection is made directly to the 230V mains supply.



TECHNICAL DATA

| | |
|-----------------------------|-------------------|
| Item no. | 114271 |
| Rotating or tilting | tiltable |
| IP Code | IP 20 |
| Assembly | Recessed |
| Assembly details | Ceiling |
| Primary nominal voltage | 220-240V ~50/60Hz |
| Secondary power / voltage | 700 mA |
| Safety class | II |
| Wattage | 29 W |
| Minimum ambient temperature | -25 °C |
| Maximum ambient temperature | 35 °C |
| Network rated standby power | 0.33 W |
| Level of inrush current | 15 A |
| Duration of inrush current | 100 µs |
| Stroboscopic effect (SVM) | 0 |
| Lumen | 2700 lm |
| Colour temperature | 3000 Kelvin |
| Beam angle | 30 ° |
| Color | white |
| CRI | 80 |
| LXXBXX data | L70B50 |
| Service life | 30000 h |

Light Source

| | |
|--------|---|
| 916475 |  |
|--------|---|

| | |
|-----------------------|----------|
| Height | 9.5 cm |
| Diameter | 18 cm |
| Net weight | 0.908 kg |
| Gross weight | 1.051 kg |
| Shape of cut-out | round |
| Installation depth | 10 cm |
| Installation diameter | 15 cm |