




PATTA-I recessed fitting

LED, 3000K, round, matt white, 38°, incl. driver

The innovative PATTA I recessed fitting is suitable for ceiling thicknesses of up to 25 mm. Rated IP65 it can be used outdoors or in damp areas. This set is available in matt black, matt white, or brushed aluminium as well as in round or square form. Equipped with a powerful, warm white premium COB LED in a rigid mount, as well as the dimmable LED driver included in the scope of supply, the set can be used in any lighting situation. The electrical connection is made directly to the 230V mains supply.



Tekniske data

Item no.	114421
IP klasse	IP20/IP65
Montering	Recessed
Monterings detaljer	Ceiling
Dæmpbar	Ja
Dæmpningstype	Leading edge, trailing edge
Primær spænding	220-240V ~50/60Hz
Sekundær strøm / spænding	500mA
IP Tæthedegrad	II
Watt	11 W
Lumen	910 lm
Farvetemperatur	3000 Kelvin
Spredningsvinkel	38 °
Farve	white
CRI	80
LXXBXX-data	L70B50
Højde	4.5 cm
Diameter	8 cm
Nettovægt	0.254 kg
Bruttovægt	0.299 kg
Indbygningsdybde	6 cm
Installations diameter	6 cm

Lyskilde

916451		BIG WHITE side	245
--------	---	----------------	-----